

# PB シリーズ

## FR4 ガラスエポキシ製タグ

FR4 ガラスエポキシは、難燃性と低伝導率の素材。  
PB シリーズは大小さまざまなサイズ品をラインアップ、  
コストパフォーマンスに優れた製品です。

- 【共通仕様】
- 外装材質：FR4(PCB)
  - 取付素材：金属
  - 動作温度範囲：-20 ~ 100°C
  - 保存温度範囲：-20 ~ 150°C
  - IC Type: Alien Higgs 3/ NXP Ucode8 他

製品名	サイズ (mm)	読取距離 (参考)
 PB-D05	5 Φ × 4	0.4 m
 PB-D06	6 Φ × 4	0.4 m
 PB-D10	10 Φ × 3	0.6 m
 PB-D13	13 Φ × 2.8	1.2 m
 PB-D16	16 Φ × 3	1.2 m
 PB-D20	20 Φ × 2.8	1.5 m
 PB-D40	40 Φ × 3	3.3 m
 PB-0603t	6 × 3 × 3	0.4m
 PB-0603	6 × 3 × 4	0.4m
 PB-0606	6 × 6 × 3	0.5m
 PB-0803	8 × 3 × 4	0.5m
 PB-1004	10 × 4 × 2	0.6m
 PB-1204	12 × 4 × 2.5	0.6m
 PB-1307	13 × 7 × 3	1.2m
 PB-1504	15 × 4 × 2	1.1m
 PB-1806	18 × 6 × 3	1.2 m
 PB-2208	40 × 10 × 2	2.2 m

製品名	サイズ (mm)	読取距離 (参考)
 PB-2510	25 × 10 × 2	1.2 m
 PB-3005	30 × 5 × 2	1.2 m
 PB-3310	33 × 10 × 2	1.5 m
 PB-3613	36 × 13 × 3.5	2.3 m
 PB-4010	40 × 10 × 2	2.2m
 PB-5010	50 × 10 × 1	1.4m
 PB-5213	52 × 13 × 3.5	4m
 PB-6020	60 × 20 × 3.5	4.5m
 PB-6604	66 × 4 × 3	0.5m
 PB-7020	70 × 20 × 3.6	5m
 PB-7035	70 × 35 × 3.7	5.5m
 PB-7525	75 × 25 × 3.0	6.3m
 PB-8008	80 × 8 × 3.5	2m
 PB-8020	80 × 20 × 3.5	4.5m
 PB-8520	85 × 20 × 1.6	10m
 PB-9020	90 × 20 × 3.6	5m
 PB-9525	95 × 25 × 3.6	4.5m

※カタログ記載の仕様は、予告なく変更される場合があります。